

Ovale Aufhängeglieder,


ohne Abflachung, Güteklasse 8, rot lackiert

Art. Nr. 31a...



WIEDENMANN
... weil viel davon abhängt!

Nenn- größe	Anschlagketten DIN 5688-8		Anschlagseile EN 13414-1		d mm	l mm	w mm	Trag- fähig- keit kg	kg / Stück
	1-Strang	2- Strang	1-Strang	2-Strang					
	Nenngr.	Nenngr.	SeilnennØ	Seilnenn Ø					
A 13	6/7-8	6-8	8/10	8/10	13	90	50	1.680	0,3
A 16	8-8	7-8	12/14	12	16	110	60	2.500	0,5
A 18	10-8	8-8	16/18	14	18	130	70	3.300	0,8
A 20	-	10-8	-	-	20	140	80	4.350	1,1
A 22	13-8	-	20/22	16/18	22	160	90	5.650	1,5
A 26	16-8	13-8	24/26/28	20/22	26	180	100	8.400	2,3
A 32	18/19/20-8	16-8	32	24	32	230	125	12.500	4,4
A 36	22-8	18-8	36	26/28	36	250	140	16.000	6,2
A 40	-	19/20-8	-	32	40	290	160	18.000	8,8
A 45	26/28-8	22-8	-	36	45	320	175	25.000	12,0
A 50	32-8	26-8	-	-	50	340	190	31.500	16,0
A 56	36-8	32-8	-	-	56	400	200	45.000	23,0
20 B7	10-8	7/8-8	-	-	20	170	90	6.500	1,3
22 B7	10/13-8	10-8	-	-	22	210	110	7.200	1,8
28 B7	13/16-8	13-8	-	-	28	270	140	11.800	3,8
32 B6	20-8	16-8	-	-	32	270	140	17.100	5,1
38 B7	22-8	20-8	-	-	38	420	220	19.100	10,8
45 B7	26-8	22-8	-	-	45	470	250	27.600	16,6



WIEDENMANN

... weil viel davon abhängt!

90431 Nürnberg
Egenhauser Str. 5
Tel +49 (0)911 6109530
Fax +49 (0)911 652032

97342 Marktstett
Am Traugraben 8
Tel. +49 (0)9332 50610
Fax +49 (0)9332 506118

06796 Sandersdorf
OT Brehna/Delitzscher Str. 5
Tel. +49 (0)34954 90960
Fax +49 (0)34954 909619

42859 Remscheid
Rosenhügeler Str. 28
Tel. +49 (0)2191 6925460
Fax +49 (0)2191 6925461

info@ws-gruppe.de

www.ws-gruppe.de

shop.ws-gruppe.de